



HIGH VOLTAGE STACK BATTERY

4.8kWh-12kWh
Power-Core

Enershare Battery Core
Up to 6 towers in parallel
From 4.8 kWh to 72kWh

Enershare Tech Company Limited

Tel: 0086-755-28748610 E-mail: info@enershare.cn

<https://www.enershare.cn>

The EnerShare Battery Core Series

EnerShare Battery Core Series, Sparkling With Innovation, Provides You With Intelligent Integration Storage Solutions. They Can Handle Up To A Voltage Of 600 V Sharing Our Minted Smart BMS.

EnerShare Battery Core Series Will Inaugurate a New Era In The Residential Energy Storage Industry.

EnerShare Power-Core

Usable Energy: 4.8~12 kWh
Nominal Voltage: 204V ~ 512V
Stacks: 2-5 Battery



Smart System Design

- LFP Chemistry
- Automatic Inverter Configuration (set-up free)
- Automatic Battery System Configuration (set-up free)
- Intelligent Display (Key Info, Err code, SOC)
- Power and Energy for all applications
- 1 and 3 phase, on / off grid / back up support
- No DC/DC, high efficiency system layout
- Up to 6 towers in parallel



Smart Installation Design

- Stackable Design, Easy Installation, $\leq 36.5\text{kg}$ / Stack
- Slim and Compact
- Plug-Play (Direct Connect RJ45)
- Aluminum Housing
- IP65 Protection

EnerShare Power-Core is a Power Type With a Capacity Of 2.4 KWh, 102.4 V In Each Battery Stack.

Smart BMS



Operating Voltage Range	120~600V
Max Output Current	30 A
Peak Output Current	50 A (5s)
Communication	CAN 2.0/ RS485
Dimensions (H/W/D)	175* 650* 260 mm
Weight	≤ 20 kg



Battery	Power-Core
Usable Energy	2.4 kWh
Rated Capacity	23.5Ah
Battery Cell Technology	LFP
Operation Temperature	-10~55 °C
Nominal Voltage	102.4 V
Operating Voltage Range	86.4~116.8 V
Max Output Current	25 A
Peak Output Current	50 A (5s)
Dimensions (H/W/D)	175* 650* 260 mm
Weight	≤ 35 kg

Stackable

Up to 2-5 battery 4.8kWh-72kWh

Increase the capacity freely in lifetime It grows as your family grows


LCD Screen



EnerShare

Smart BMS

Invisible Handles



IP65

Aluminum Case

Battery Stacks


Base & Legs

Stackable battery units with direct connection
No additional Wires, No additional Screws

1 Person Work
Time saving, Cost Saving

High Scalability, Able To Be Paralleled Up To 6 Towers

Wide capacity options from 4.8kWh to 72kWh




EnerShare **Power-Core**



EnerShare Power-Core

4.8KWh-12KWh High Voltage Stack Battery



Technical Specification

Number of Stacks	2	3	4	5
Usable Energy	4.8 kWh	7.2 kWh	9.6 kWh	12 kWh
Max Output Current	25 A			
Peak Output Current	50 A (5s)			
Nominal Voltage	204.8 V	307.2 V	409.6 V	512 V
Operating Voltage Range	172.8~233.6 V	259.2~350.4 V	345.6~467.2 V	432~584 V
Scalability	Up to 6 towers (From 4.8 kWh to 72 kWh)			
Dimensions (H*W*D) (mm)	625* 650* 260mm	800* 650* 260mm	975* 650* 260mm	1150* 650* 260mm
Weight	90 kg	125 kg	160 kg	195 kg
Operation Temperature	-10~55 °C			
Protection Rating	IP65			
Round-trip Efficiency	≥ 96 %			
Certification & Compliance	UKCA / IEC62619 / VDE / CE / UN38.3			
Applications	ON Grid / ON Grid Backup / OFF Grid			
Warranty	10 Years			


Set up Free

Instantly functioning after installation,
No App, No laptop commissioning

Automatic recognition between systems



inverter



EnerShare Battery Core Series Battery Compatible Inverter List V1.5

Inverter		Stack Quantity		Minimum Firmware Version	
		Power-Core	Energy-Core	Inverter	Battery Core
					BMS
GoodWe	ET (5-10kW) ET (40-50KW)	2-5	4-8	≥ ARM 13	≥ V1.6-1.5
	BT	2-5	4-8	≥ ARM 13	
	EH/BH	2-3	3-6	≥ ARM 07	
	EHB	2-4	3-6	≥ ARM 03	
Solis	S6-EH3P (3-50)K-H	2-5	3-8	≥ V02	≥ V1.6-1.5
Deye /Sunsynk	SUN-(5-50) K-SG01HP3-EU	2-5	3-8	≥ 2001-C01B	≥ V1.6-1.5
Solinteg	MHS-3-8K	2-5	3-8		≥ V1.6-1.5
	MHT-4-20K	2-5	3-8		
hoymiles	HYT-(5.0-12.0) HV-EUG1	2-5	3-8	≥ V01.00.06	≥ V1.8-1.5
	HAT-(5.0-10.0) HV-EUG1	2-5	3-8	≥ V01.00.06	
Afore	AF3-20K-TH	2-5	3-8		≥ V1.8-1.5
	AF3-20K-MTH				
Sinexcel	Isuna 5000-20000T	2-5	3-8		≥ V1.8-1.5
MEGAREVO	R(6~15)KH3-P	2-5	3-8		≥ V1.8-1.5

Note:

1. Maximum 6 Systems In Parallel Connection. For Parallel Connection, The Below Requirements Must Be Fulfilled:

a) Enershare Power-Core CANNOT Be Parallel Connected With Enershare Energy-Core ; b) Each Of The Parallel Connected System Must Have The Same Stack Quantity.